

PLAZA™

PLUS

Sealer / Finish for hard floors

*Long lasting, high gloss
sealer/finish specifically
formulated for stone floors.*

Simplifies Stone Floor Maintenance

One product seals and finishes. Can be applied, maintained and removed like any conventional finish.

Improves Appearance Of Your Stone Floors

Excellent leveling and brilliant gloss that can withstand high traffic loads.

Easy-To-Use

Offers excellent adhesion to new or worn stone flooring. Apply using a mop and maintain with 175-1500 rpm equipment.

Extreme Versatility

A one-product solution for multiple stone substrates, including marble, terrazzo, granite, slate, quarry tile, brick, unglazed ceramic, Mexican tile, and others.



Johnson wax
PROFESSIONAL

PLAZA™ PLUS SEALER / FINISH

Profile

WHAT IS IT?	PLAZA™ Plus Sealer/Finish is a new, high performance sealer/finish, which offers excellent adhesion to new or worn granite, marble, terrazzo and other stone flooring. PLAZA™ Plus Sealer/Finish contains a blend of unique polymers which create a durable coating that can withstand high traffic loads.
WHAT DO I USE IT ON?	Use on marble, terrazzo, quarry tile, brick, slate, unglazed ceramic and Mexican tile. PLAZA™ Plus Sealer/Finish can also be used on resilient floors.
HOW DO I USE IT?	When used as a sealer/finish, PLAZA™ Plus Sealer/Finish can be maintained with either low speed or UHS equipment. When used as a sealer, PLAZA™ Plus Sealer/Finish can be top-coated with other Johnson Wax Professional finishes to meet specific performance requirements.
PRECAUTIONS:	Do not use on wood, cork, and glazed ceramic tile. Do not dilute. Do not use on surfaces colder than 50°F/10°C. To avoid contamination, do not return unused product to original container.

Specifications

Fragrances:	Mild Ammoniacal
Color/Form:	Milky-white liquid
pH:	8-8.6
Solubility in Water:	dispersable
Specific Gravity (water = 1):	1.03
Non-Volatile Solids:	19.8 - 20.2%
Flash Point:	none
Shelf Life:2 years
Drying Time:	approx. 60 minutes
Slip Resistance:0.5 minimum (ASTM D2047)
Coverage: first coat up to 1500 sq. ft. per gal. (40 m ² per liter); successive coats - 2000-2500 sq. ft. per gal. (50-60 m ² per liter)	

HMIS Hazard Ratings:

Health	1
Flammability	0
Reactivity	0

Safety Reminder

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDS's are available on line at www.jwp.com or by calling 1-888-352-2249.

Applications

Sealer/finish that can be used on new or worn marble, terrazzo, granite, quarry tile, brick, slate, unglazed ceramic, Mexican tile and other stone floorings. Exhibits exceptional adhesion, gloss, and durability.



Packaging

PACK / SIZE	PRODUCT CODE
4 - 1 gal. / 3.78 L Containers	4168
1 - 5 gal. / 18.9 L ENVIROBOX™	4171

Johnson wax
PROFESSIONAL

FOR COMMERCIAL & INDUSTRIAL USE ONLY

© 2003 JohnsonDiversey, Inc., Sturtevant, WI 53177-0902. All Rights Reserved.

For further information on special applications or other Johnson Wax Professional products, contact your JohnsonDiversey representative, at 1-800-558-2332 or visit our web-site at www.johnsondiversey.com