

BRavo
1500+



Floor Stripper

Specially formulated to effectively and consistently remove the routine buildup of toughened finishes that accompany High Speed and Ultra High Speed floor care machines.



Powerful Stripping Action

Quickly penetrates and emulsifies finish.

Reduces Labor

Strips the accumulation of finish that normally accompanies high and ultra high speed floor care programs, reducing labor.

Low Foam Formula

Results in less time emptying pickup tanks.



Johnson wax
PROFESSIONAL

BRAVO® 1500+ FLOOR STRIPPER

Profile

WHAT IS IT?	A non-ammoniated floor stripper specially formulated for high and ultra high speed floor care programs
WHAT DO I USE IT ON?	Recommended for use on resilient and non-resilient floors except unsealed wood, linoleum, cork and painted surfaces.
HOW DO I USE IT?	1. Use appropriate personal protective equipment. For light build-up of finish use at a dilution of 1:8. For heavy build-up use at a dilution of 1:2 to 1:6. 2. Apply liberal amounts of solution uniformly to floor with a mop. Start with the edges to give them more soak time. If splashing occurs, wipe off surfaces with a clean rag dampened with water. 3. Let stripper solution soak for 7-10 minutes. Re-wet as necessary, do not allow solution to dry on floor. Longer soak times may be necessary in cases of extreme buildup. 4. Hand or machine scrub thoroughly using black pads or stripping brush. 5. Pick-up all of the solution with a clean mop, wet vac or automatic scrubber. Mop up any "tracks" left by wet vacs or automatic scrubbers before they dry. 6. Thoroughly rinse floor with clear water. 7. Let floor dry completely before applying recommended JOHNSON WAX PROFESSIONAL brand floor sealer or finish.
CAUTIONS:	Do not use on wood floors or painted surfaces. Test for softening or color bleeding on linoleum, rubber, or asphalt floors. Use in well ventilated areas. Do not use for selective stripping of finish on TECHNIQUE® sealer.

Specifications

Color / Form	Clear / Liquid
Fragrance:	Characteristic
pH:	>13
Dilution:	1:4 (may also be used 1:2 or 1:3 for heavy buildup and 1:8 for light or medium buildup.)
Shelf Life:	2 years
VOC's	The VOC content of this product, or it's minimum use dilutions where applicable, complies with current California Air Resources Board (CARB) regulations.

HMIS Hazard Ratings:

	concentrate
Health	3
Flammability	0
Reactivity	0

Safety Reminder

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDS's are available on line at www.johnsondiversey.com or by calling 1-888-352-2249.



Packaging

PACK / SIZE	PRODUCT CODE
4 / 1 Gallon (3.78 L) Containers	4639
1 / 5 Gallon (18.9 L) ENVIROBOX™	4638

Johnson wax
PROFESSIONAL

FOR COMMERCIAL & INDUSTRIAL USE ONLY

© 2003 JohnsonDiversey, Inc., Sturtevant, WI 53177-0902. All Rights Reserved.

For further information on special applications or other Johnson Wax Professional products, contact your JohnsonDiversey representative, or call us at 1-800-558-2332 or visit our web-site at www.johnsondiversey.com

Bravo is used under authority from S.C. Johnson & Son, Inc. Racine, Wisconsin, U.S.A.