

**ATTAC**<sup>®/MD</sup>

# Floor Stripper

*For the professional's  
toughest stripping jobs!*



## Reduced Labor and Costs

Formulated to work the first time to reduce "restrips".

## One Product For All Your Stripping Needs

Use at 1:12 to 1:16 for economical, light duty stripping.  
Use at 1:4 to 1:8 for removing the toughest build-ups  
without gumming up.

## User Friendly

- Works best in cool water
- Low foam, free rinsing
- No harsh ammonia odor
- Non-flammable



**Johnson wax**  
**PROFESSIONAL**

# ATTAC<sup>®/MD</sup> FLOOR STRIPPER

## Profile

<b>WHAT IS IT?</b>	A non-ammoniated floor stripper specially formulated for high and ultra high speed floor care programs.
<b>WHAT DO I USE IT ON?</b>	Recommended for use on most resilient and non-resilient floors except as noted below under "important." Always refer to product label for precautionary and use instructions.
<b>How do I use it?</b>	1. Use appropriate personal protective equipment. For light build-up of finish use at a dilution of 1:12 to 1:16. For heavy build-up use at a dilution of 1:4 to 1:8. 2. Apply liberal amounts of solution uniformly to floor with a mop. Start with the edges to give them more soak time. If splashing occurs, wipe off surfaces with a clean rag dampened with water. 3. Let stripper solution soak for 5-10 minutes. Mop agitate to loosen finish. Re-wet as necessary, <b>do not allow solution to dry on floor</b> . Longer soak times may be necessary in cases of extreme buildup. 4. Hand or machine scrub thoroughly using black pads or stripping brush. 5. Pick-up all of the solution with a clean mop, wet vac or automatic scrubber. 6. Mop up any "tracks" left by wet vacs or automatic scrubbers before they dry. Thoroughly rinse floor with clear water, using a mop and bucket. 7. Let floor dry completely before applying recommended JOHNSON WAX PROFESSIONAL brand floor sealer or finish.
<b>IMPORTANT:</b>	Do not use on wood, marble or painted surfaces. Test for softening or color bleeding on linoleum, rubber, or asphalt floors. Use in well ventilated areas. Do not use for selective stripping of finish on TECHNIQUE <sup>®</sup> sealer.

## Specifications

Color / Form	Clear white to yellowish / Liquid
Fragrance:	Mild
pH:	>13 (Basic)
Dilution:	1:4 to 1:8 for heavy buildup or 1:12 to 1:16 for light buildup
Specific Gravity:	1.02
Freezing Point:	<0°C / 32°F

### HMIS Hazard Ratings:

concentrate

Health	3
Flammability	0
Reactivity	0

### Reactivity/Réactivité

4=Very High/Extrême; 3=High/Haut;

2=Moderate/Moderé; 1=Slight/Sans gravité 0=Insignificant/Aucun

## Safety Reminder

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDS's are available on-line at [www.johnsondiversey.com](http://www.johnsondiversey.com) or by calling 1-888-352-2249.



## Packaging

PACK / SIZE	PRODUCT CODE
4 / 3.78 L Containers	54260
1 / 18.9 L ENVIROBOX™	54261

**Johnson wax**  
PROFESSIONAL

FOR COMMERCIAL & INDUSTRIAL USE ONLY

© 2004 JohnsonDiversey, Inc., Sturtevant, WI 53177-0902. All Rights Reserved.

For further information on special applications or other Johnson Wax Professional products, contact your JohnsonDiversey representative, or call us at 1-800-558-2332 or visit our web-site at [www.johnsondiversey.com](http://www.johnsondiversey.com)